





⇒ Return completed application to:

APPLICATION FOR CERTIFICATE OF COMPLIANCE FOR SMOKE DETECTORS AND CARBON MONOXIDE ALARMS M.G.L. CHAPTER 148, SECTIONS 26F, 26F1/2

City or Town	Edgartown	Date:			
Application is herel	by made for inspection of smoke of	detectors and carbon monoxide alarms as required by			
Massachusetts General Law, Chapter 148, Sections 26F, 26F1/2 and 527 CMR 1:00 Section 13.7.					
NOTE: SUBMIT A	NOTE: SUBMIT APPLICATION TO LOCAL FIRE DEPARTMENT HEADQUARTERS				
Location of Property					
Owner of Property					
		Signature of Applicant			
Inspection/Testing	completed on:	By:(Inspector)			
Fee: (M.G.L. Chap	ter 148 Sec. 10A)	Fire Chief Alexander J. Sch	aeffer		
Note: Any certifica		sions of M.G.L. Chapter 148, Sections 26F, 26F1/2 expire			
	FIRE	DEPARTMENT'S COPY			
2					
FP-007C	The Commo	nwealth of Massachusetts ofEdgartown			
(Rev. 1.2018)		CATE OF COMPLIANCE ER 148, SECTIONS 26F, 26F1/2			
City or Town:	Edgartown	Date:			
		and carbon monoxide alarms* and was found to be in cor 26F, 26F1/2 and 527 CMR 1.00 Section 13.7.	mpliance with		
Inspection/Testing	completed on:	By:(Inspector)			
Fee Paid:	Head of Fire Department	Alexander J. Schaeffer			

Note: This certificate expires sixty (60) days after date of issue.

YEAR BUILT:	
-------------	--

August 27, 1997?	Yes	No
August 27, 1997:	168	NO
(If yes, proceed to residence permitted after August 27, 1997)		
Has a garage addition been added to the residence since January 1, 2008?		
(If yes, see heat detector requirements for January 1, 2008)	Yes	No

RESIDENCES CONSTRUCTED PRIOR TO JANUARY 1, 1975

Smoke Alarms are required as follows:

Existing Smoke Alarms

On every level of the residence including basements & cellars. On the ceiling, at the base, of each stairway.

On the ceiling outside of each separate sleeping area. Smoke alarms may be battery operated, hardwired or combination of the two.

If the smoke alarm is located within 20' of a kitchen or bathroom (containing a tub or shower) it must be photoelectric. If the smoke alarm is outside of 20' to a kitchen or bathroom (containing a tub or shower), you must utilize either a dual alarm (containing both technologies: ionization and photoelectric) or two separate alarms (one photoelectric and one ionization).

Newly Installed Smoke Alarms

On every level of the residence including basements and cellars. On the ceiling, at the base, of each stairway.

On the ceiling outside of each separate sleeping area. Smoke alarms may be either battery operated, hardwired or combination of the two.

Battery powered alarms must have 10 year, non-rechargeable, non-replaceable batteries.

Must contain a hush feature to silence nuisance alarms. Must be photoelectric. Can be in combination with ionization or carbon monoxide.

House Numbers: Must be posted on the house; must be visible from the street, if not or is greater than 100' from the street, then the number must also be posted at the street and visible from both directions; numbers must be a minimum of 3"in height; high contrast (black on white preferred over brass on white).

Carbon Monoxide Alarms are required as follows:

•	On every level of the residence, including habitable portions of basements and attics*, and		
	they must be located within 10 feet of each bedroom door.	()
•	Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice may		
	be used anywhere.	()
•	Combination alarms (ionization smoke and carbon monoxide) with voice may be used, if		
	the alarm is outside of 20 feet of a kitchen or bathroom (containing a bathtub or shower).	()
•	May be either: battery powered, plug-in with battery backup, hardwired with battery		
	backup or system type.	()
•	Follow the manufacturer's instructions for placement.	()

*Habitable portions of basements and attics: If there is a finished portion of the basement or attic that is partitioned off from the rest of the space, an additional alarm must be in that portion. If the basement is unfinished but has habitable areas such as: a work bench, exercise equipment, pool table, sitting area etc., then a carbon monoxide alarm is required.

Edgartown Fire Department PO Box 2097 Edgartown, MA 02539 508-627-5167

Alexander J Schaeffer Fire Chief

RESIDENCES PERMITTED FOR CONSTRUCTION BETWEEN JANUARY 1, 1975 AND AUGUST 26, 1997

Smoke Alarms are required as follows:		
 One smoke alarm on every level of the residence including basements and cellars. One smoke alarm on the ceiling outside of each separate sleeping area. 	()
 One smoke alarm on the ceiling at the base of each stairway. Please note: a smoke alarm on the ceiling outside a separate sleeping area can fulfill this requirement. 	()
 Minimum of one smoke alarm must be installed for every 1,200 sq. feet area per level. 	()
 Must be hardwired interconnected smoke alarm. 	()
Note: Any smoke alarm more than ten years old shall be replaced with a new smoke alarm. Although ionization alarms are allowed anywhere within the residence, during this time period, it is recommended that the new alarms comply with the 20 foot rule. If utilizing a combination smoke/CO alarm that is hardwired, they must comply with the CO requirements below. This requirement does not apply to low voltage alarm system smoke detectors.		
Carbon Monoxide Alarms are required as follows:		
• On every level of the residence, including habitable portions of basements and attics* and must be located within 10 feet of each bedroom.	(`
 Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice may be used 	()
anywhere.	()
• Combination alarms (ionization smoke and carbon monoxide alarm) with voice may be used,	,	`
 if the alarm is outside of 20 feet to a kitchen or bathroom (containing a bathtub or shower). May be either: battery powered, plug-in with battery backup, hardwired with battery backup 	()
or system type.	()
Follow the manufacturer's instructions for placement.		
*Habitable portions of basements and attics: If there is a finished portion of the basement or attic that is off from the rest of the space, an additional alarm must be in that portion. If the basement is unfinished be habitable areas such as: a work bench, exercise equipment, pool table, sitting area etc., then a carbon mor alarm is required. House Numbers: Must be posted on the house; must be visible from the street, if not or is greater than 10 street, then the number must also be posted at the street and visible from both directions; numbers must be minimum of 3"in height; high contrast (black on white preferred over brass on white).	out l noxi o' fr	nas de

Edgartown Fire Department PO Box 2097 Edgartown, MA 02539 508-627-5167

Alexander J Schaeffer Fire Chief

RESIDENCES PERMITTED FOR CONSTRUCTION BETWEEN AUGUST 27, 1997 AND DECEMBER 31, 2007

Smoke Alarms are required as follows:

•	One smoke alarm on every level of the residence including basements and cellars.	()
•	One smoke alarm outside each separate sleeping area.	()
•	One smoke alarm in each bedroom.	()
•	A minimum of one smoke alarm for every 1,200 sq. feet area per level.	()
•	Must be hardwired and interconnected smoke alarms with battery backup.	()
•	If smoke alarm is within 20 feet of a kitchen or bathroom (containing a bathtub or shower), the		
	smoke alarm is required to be photoelectric only.	()
•	Smoke alarms shall be a minimum of 36" away horizontally from HVAC supply vent, ceiling fan blade tip, or bathroom door with a shower or tub.	()
	Note: Any smoke alarm more than ten years old shall be replaced with a new smoke alarm. All smoke alarms must be the same brand. Also if utilizing a combination smoke/CO alarm that is hardwired, they must comply with the CO requirements below. This requirement does not apply to low voltage alarm system smoke detectors.		
	The second secon		
	Carbon Monoxide Alarms are required as follows:		
•	Carbon Monoxide Alarms are required as follows:		
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and	()
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom.	()
	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and	()
	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom. Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice, may	()
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom. Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice, may be used anywhere.	()
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom. Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice, may be used anywhere. Combination alarms (ionization smoke and carbon monoxide alarm) with voice may be used if the alarm is outside of 20 feet to a kitchen or bathroom (containing a bathtub or shower).	())
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom. Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice, may be used anywhere. Combination alarms (ionization smoke and carbon monoxide alarm) with voice may be used if the alarm is outside of 20 feet to a kitchen or bathroom (containing a bathtub or shower). May be either: battery powered, plug-in with battery backup, hardwired with battery	()
•	Carbon Monoxide Alarms are required as follows: On every level of the residence, including habitable portions of basements and attics*, and must be located within 10 feet of each bedroom. Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice, may be used anywhere. Combination alarms (ionization smoke and carbon monoxide alarm) with voice may be used if the alarm is outside of 20 feet to a kitchen or bathroom (containing a bathtub or shower).	(((((((((((((((((((())

*Habitable portions of basements and attics: If there is a finished portion of the basement or attic that is partitioned off from the rest of the space, an additional alarm must be in that portion. If the basement is unfinished but has habitable areas such as: a work bench, exercise equipment, pool table, sitting area etc., then a carbon monoxide alarm is required.

House Numbers: Must be posted on the house; must be visible from the street, if not or is greater than 100' from the street, then the number must also be posted at the street and visible from both directions; numbers must be a minimum of 3"in height; high contrast (black on white preferred over brass on white).

Edgartown Fire Department PO Box 2097 Edgartown, MA 02539 508-627-5167

Alexander J Schaeffer Fire Chief

RESIDENCES PERMITTED FOR CONSTRUCTION FROM

JANUARY 1, 2008 TO AUGUST 3, 2011

Smoke alarms are required as follows:

One smoke alarm on every level of the residence including basements and cellars.	()
 One smoke alarm at the base of each stairway. 	()
 One smoke alarm outside of each separate sleeping area. 	()
 One smoke alarm inside every bedroom. 	()
 A minimum of one smoke alarm must be installed for every 1,200 sq. feet area per level 	()
 Must be hardwired and interconnected smoke alarms with battery backup. 	()
• If the smoke alarm is within 20 feet of a kitchen or bathroom (containing a bathtub or shower),		
the smoke alarm is required to be a photoelectric only & located a min. of 36" from bathroom do)
• If the smoke alarm is greater than 20 feet from a kitchen or a bathroom (containing a bathtub or		
shower), the smoke alarm is required to be either a photoelectric alarm or a dual alarm		
(containing both ionization and photoelectric technologies).	()
 Smoke alarm shall be a minimum of 36" horizontally from HVAC supply vent, ceiling fan blade ti 	p, or	
bathroom door with a shower or tub.	()
Note: Any smoke alarm more than ten years old shall be replaced with a new smoke		
alarm. All interconnected smoke alarms must be the same brand. Also if utilizing a		
combination smoke/CO alarm that is hardwired, they must comply with the CO requirer	nent	
below. This requirement does not apply to low voltage alarm system smoke detectors.		
Carbon Monoxide Alarms are required as follows:		
 On every level of the residence and located within 10 feet of each bedroom door. 	()
 Combination alarms (photoelectric smoke and carbon monoxide alarm) with voice 		
may be used.	()
 Must be hardwired and interconnected with battery backup (may be separately wired from the 		
existing smoke alarm system).	()
• If there is a finished portion in the basement or attic, then the alarm must be in that portion.	()
Heat Detectors are required as follows:		
• In any attached garage or integral garage (garage under) a heat detector listed for the ambient		
temperature shall be installed.	()
 New addition garages, to an existing dwelling, a heat detector shall be installed and interconnect 	.ed	
to any existing compatible smoke detection system. If there is no compatible smoke detection		
system present, an additional heat detector with sounding device or a separate sounding device		
shall be installed in the dwelling within 20 feet of the door from the garage to the dwelling.	()
House Numbers: Must be posted on the house; must be visible from the street, if not or is greater than	100' f	rom the
street, then the number must also be posted at the street and visible from both directions; numbers must		com tm
minimum of 3"in height; high contrast (black on white preferred over brass on white).		
Edgartown Fire Department		
PO Roy 2007 Edgartown MA 02520		

508-627-5167

Alexander J Schaeffer Fire Chief Joshua Baker Fire Prevention Officer

RESIDENCES PERMITTED FOR CONSTRUCTION FROM AUGUST 4, 2011 TO THE PRESENT

Smoke alarms are required as follows:

	Smoke diarms are required as follows.		
• O	ne smoke alarm on every level of the residence including basements and cellars.	()
	ne smoke alarm at the base of each stairway.	()
	ne smoke alarm outside of each separate sleeping area.	()
	ne smoke alarm inside every bedroom.	()
• A	minimum of one smoke alarm must be installed for every 1,200 sq. feet area per level.	()
• M	lust be hardwired and interconnected smoke detectors with battery backup.	()
	ll smoke alarms are required to be photoelectric and must be the same brand.	()
	moke alarm shall be a minimum of 36" horizontally from HVAC supply vent, ceiling		
Fa	an blade tip, or bathroom door with a shower or tub.	()
al co	ote: Any smoke alarm more than ten years old shall be replaced with a new smoke larm. Also if utilizing a combination smoke/CO alarm that is hardwired, they must omply with the CO requirements below. This requirement does not apply to low oltage alarm system smoke detectors.		
	Carbon Monoxide Alarms are required as follows:		
	n every level of the residence and located within 10 feet of each bedroom door.	()
	ombination alarms (photoelectric smoke and carbon monoxide alarm) with voice hay be used.	()
	lust be hardwired and interconnected with battery backup (may be separately wired from the		
	xisting smoke detection system).	()
• If	there is a finished portion in the basement or attic, then the alarm must be in that portion.	()
	Heat Detectors are required as follows:		
te	any attached garage or integral garage (garage under) a heat detector listed for the ambient emperature shall be installed. ew addition garages, to an existing dwelling, a heat detector shall be installed and interconnected	()
	any existing compatible smoke detection system. If there is no compatible smoke detection system present, an additional heat detector with sounding device or a separate sounding device		
sh	nall be installed in the dwelling within 20 feet of the door from the garage to the dwelling.	()
street, the	Imbers: Must be posted on the house; must be visible from the street, if not or is greater than 100 n the number must also be posted at the street and visible from both directions; numbers must be of 3"in height; high contrast (black on white preferred over brass on white).		om the

Edgartown Fire Department PO Box 2097 Edgartown, MA 02539 508-627-5167

Alexander J Schaeffer Fire Chief Joshua Baker Fire Prevention Officer

CLOSING DATE:		
PROPERTY ADDRESS:		
CONTRACTINANT		
CONTACT NAME:		
AGENCY NAME:		
AGENCI NAME.		
PHONE NUMBERS:		Cell
		Office or other
		Email
Complete all 1	pages that pertain to the property bei	ng sold
, ,	er or placement of smoke alarms or co tion Officer for clarification. This doc	
guideline and is not all-inclusive of	fall regulations relative to residential	smoke alarms and carbon
monoxide detectors. A re-inspect compliance checklist have not l	ion fee will be assessed, if any of the been complied with.	he items on the foregoing
-	F. C.	
	Signed:	
	<i></i>	
	<i></i>	
	<i>-</i>	
	J	
	Edgartown Fire Department PO Box 2097 Edgartown, MA 02539	